



200W Single Output Switching Power Supply

EP-200W-12V

MPN: OMP-EP200PFC-12V



Features:

- * Constant Voltage
- * Variable AC input 90-277 VAC
- * IP68 construction with waterproof enclosure
- * Suitable for Dry, Damp and Wet Location
- * Protection: Short Circuit / Over Temp. / Over Voltage
- * Aluminum Case
- * 100% full load burn-in test
- * 5 years warranty
- * LLC current resonant technology with 92-96% efficiency, reduced size and increased reliability.



| | | |
|-------------|--------------------------|-----------------------------|
| INPUT | VOLTAGE | AC90V - 277V |
| | AC CURRENT | 2A@115VAC, 0.94A@240VAC |
| | FREQUENCY | 50/60Hz |
| | INRUSH CURRENT | 50A |
| | POWER FACTOR | 0.98 min. |
| | POWER FACTOR CORRECTION | Built-in PFC |
| | THD | 10% max |
| | EFFICIENCY | 92% |
| OUTPUT | VOLTAGE | 12VDC |
| | RATED CURRENT | 16.6A |
| | LINE & LOAD REGULATION | +/-5% |
| | RIPPLE & NOISE(MAX) | 200mVp-p |
| | SETUP, RISING TIME | 1 SEC |
| PROTECTION | ENCLOSURE PROTECTION | IP68 |
| | CLASS | Class 1 |
| | SHORT CIRCUIT | Auto Restart |
| | OVER CURRENT | Auto Restart |
| ISOLATION | OVER TEMPERATURE | Auto Restart |
| | WITH STAND VOLTAGE | P-S3.75KV 10mA |
| | ISOLATION RESISTANCE | 500V 100MΩ |
| ENVIRONMENT | WORKING TEMP. & HUMIDITY | -4~122°F, 20~85%RH |
| | STORAGE TEMP. & HUMIDITY | -4~167°F, 5~95%RH |
| OTHERS | EMI | Cisper22 Class B |
| | SURGE | L-N : ±2KV / L-F.G : ±4KV |
| | DIMENSION (INCH) | 8.8 x 2.1 x 1.4 |
| | WEIGHT (LBS) | 1.4 |
| | CASE MATERIAL | Aluminum |
| | MOLDING MATERIAL | Silicon |
| | CERTIFICATE | UL879 / UL8750 - UL E528990 |
| | QTY/CTN | 10 |

